

Description: Patented Premium Engineered COREtec Plus Design™ Luxury Vinyl Plank & Tile Floating Floor with Attached Cork Underlayment

Warranty: Lifetime Limited Residential Wear Warranty
Lifetime Limited Structural Warranty
Lifetime Limited Waterproof Warranty
10 Year Limited Commercial Wear Warranty

Installation: Float or Glue Down

Size/Packaging: **Multi--Width Planks**

127mm x 914.40mm x 8mm Planks
177.80mm x 1828mm x 8mm Planks
228mm x 1828mm x 8mm Planks
1.9471m²/carton, 8 planks per carton, 15.50kgs each carton, 72 ctns per pallet

127mm x 914.40mm x 8mm Planks
177.80mm x 1828mm x 8mm Planks
228mm x 1828mm x 8mm Planks

2.60m² /carton, 10 planks per carton, 20.80kgs each carton, 54 ctns per pallet

177.80mm x 1828mm x 8mm Planks
2.81m²/carton, 12 planks per carton, 15.50kgs each carton, 60 ctns per pallet

Multi--Tone Planks

177.80mm x 1828mm x 8mm Planks
2.81m²/carton, 18 planks per carton, 22.50kgs each carton, 28 ctns per pallet

Multi--Tone Tiles

304.8mm x 914.4mm x 8 mm Tiles
2.214m²/carton, 8 planks per carton, 18kgs each carton, 30 ctns per pallet

457mm x 609.6mm x 8 mm Tiles
2.214m²/carton, 8 planks per carton, 18kgs each carton, 30 ctns per pallet

Multi--Width and Multi--Tone Tiles

152.4mm x 609.6mm x 8 mm Tiles
304.8mm x 609.6mm x 8 mm Tiles
2.72m²/carton, 20 planks per carton, 22kgs. each carton, 28 ctns per pallet

Construction:	1.7 mm virgin PVC (0.5 mm/20 mil wear surface) 5.0 mm core (Limestone, virgin PVC, wood and bamboo dust). 1.5 mm cork underlayment
Wear Finish:	2 coats UV--cured acrylic
Gloss Level:	2% -- 6%

TEST DATA

ASTM--E648 Critical Radiant Flux:	Meets or exceeds, Class 1
ASTM E492--09 Impact Sound Conduction:	IIC 62 db
ASTM E90--09 Airborne Sound Conduction:	STC 62 db
ASTM C518 Thermal Resistance:	R Value – 0.57
NALFA 3.2 Thickness Swell:	Class 4, Heavy Commercial
NALFA 3.3 Xenon Light Resistance:	Class 4, Heavy Commercial
NALFA 3.4 Cleanability--Stain Resistance:	Class 4, Heavy Commercial
NALFA 3.5 Large Ball Impact Resistance:	Class 4, Heavy Commercial
NALFA 3.6 Small Ball Impact Resistance:	Class 4, Heavy Commercial
NALFA 3.8 Dimensional Tolerance:	Class 4, Heavy Commercial
NALFA 3.9 Caster Chair:	Class 3, Commercial
NALFA 3.10 Surface Bonding:	1.31 N/mm – Exceeds Class 3 Commercial Requirement
ASTM C 1028--96 Static Coefficient of Friction:	0.68 (slip resistance) Passes ADA/OSHA standard
ASTM F--970--07 Static Load Limit:	0.004 inch – Passes at 250 psi
ASTM--F2753 Rolling Load Over Resilient FC:	0.024 inch
ASTM F 1514 Color Resistance to Heat:	Meets <8.0 Delta E Requirement
ASTM F 1515 Color Resistance to Light:	Meets <8.0 Delta E Requirement

Certifications:	CARB Compliant GREENGUARD GOLD Certified
------------------------	---



USFloors Technical Services

Created/Revised 3/11/2016